

# Forbidden Diesel Performance 6.7L Cummins Throttle Valve Delete Installation Instructions



**Please Read Instructions Thoroughly And Verify Contents Before Assembling Or Installing Any Parts!!!**

# **Forbidden Diesel Performance 6.7L Cummins Throttle Valve Delete Installation Instructions**

**Forbidden Diesel Performance Recommends that a professional automotive diesel shop or an ASE certified technician perform the installation of this coolant filter kit. If you choose to install this kit yourself, follow all safety precautions and wear eye protection.**

**By installing this throttle valve delete, you indicate that you have read this document and you agree with the terms stated below. It is the responsibility of the purchaser to follow all installation instructions, guidelines, and safety procedures supplied with this kit.**

**Forbidden diesel performance assumes no responsibility for damages occurring from misuse, abuse, improper installation, improper operation, lack of responsible care, lack of maintenance, incompatibility with other manufacturers products, or just plain stupidity on your part.**

**Caution! Never work on a hot vehicle. Serious injury such as burns can result if the engine is still hot. Allow vehicle to cool prior to installation. Always wear eye protection when working on any vehicle.**

**This product is designed for off-road vehicles only. Do not use on registered vehicles. It is up to you and you alone to check your local applicable laws to ensure proper usage of this product.**

## **Required Tools:**

- 1.) 8mm Socket**
- 2.) 10mm Socket**
- 3.) 13mm Socket**
- 4.) Flat head Screw Driver**
- 5.) Eye Protection**

## Forbidden Diesel Performance 6.7L Cummins Throttle Valve Delete Installation Instructions

**Step 1: Remove all of the connectors, Sensors, and heat shield.**



**Step 2: Loosen Intercooler pipe and separate the boot from the throttle valve.**



**Step 3: Remove the four 8mm bolts and disconnect the throttle valve**



**Step 4: Install the throttle valve delete using the four allen bolts provided in this kit (you may have to use some small washers for a tighter fit)**



**Step 5: Re-attach and tighten down the intercooler boot and pipe clamp**



## Forbidden Diesel Performance 6.7L Cummins Throttle Valve Delete Installation Instructions

**Step 6: Re-install the  
heat shield, connectors,  
and sensors**



**Step 7: secure the  
unused throttle valve  
connector with zip ties**

